
ClimaRad wall ducting and grills

Our wall ducting is available in two versions: brick-sized or surface-mounted. Depending on the outside wall one of these versions is used. For both versions two sizes of bellows are available (a short and a medium/long version). The corresponding grilles are available in various RAL colours. Other RAL colours may be available upon request.



for wall thicknesses of 220-400 mm and 300-650 mm



Short wall ducting for surface-mounted grille for wall thicknesses of 40-140 mm



Medium/long wall ducting for surface-mounted grill for wall thicknesses of 120-350 mm and 250-600 mm

Brick-sized wall ducting

The ClimaRad brick-sized grilles resemble a brick and are therefore suitable for use in masonry walls made with bricks.

Wall ducting for wall thicknesses of 220-400 mm and 300-650 mm*

Grille dimensions: 53x210 mm



Surface-mounted

ClimaRad surface-mounted grilles are specifically designed for smooth, flat walls.

Wall ducting for surface-mounted grilles are available in two types.

Short version: for wall thicknesses of 40-140 mm*

Medium/long version: for wall thicknesses of 120-350 mm and 250-600 mm*

Grille dimensions: 127x127 mm

Colours



*Wall ducting can be shortened to the correct length.



Table for pressure drop exterior grille including wall ducting

Surface- mounted grille	Flow [m³/h]	Pressure drop [Pa]
	25	0
Flow of dis-	50	7
charged air:	75	14
	100	26
	125	48
	25	0
Flow of supplied	50	5
air:	75	9
	100	18
	125	29


Brick-sized grille	Flow [m³/h]	Pressure drop [Pa]
	25	1
Flow of dis-	50	9
charged air:	75	20
	100	36
	125	47
	25	2
Flow of supplied	50	8
air:	75	11
	100	22
	125	39













 $1. \ Brick-sized \ RAL \ 8015 \ \ / \ \ 2. \ \ Surface-mounted \ galvanized \ steel \ \ / \ \ 3. \ Roof \ tile \ ducting$

4. Vertical / 5. Integrated in transom / 6. Through threshold



ClimaRad BV

Lübeckstraat 25 7575 EE Oldenzaal The Netherlands Tel. +31 (0) 541 358 130 e-mail: info@climarad.com www.climarad.co.uk





